## FLASH TRAC OBD

#### Fully Featured Integrated GPS Tracking Platform

The Flash Trac OBD system is a fully featured integrated gps tracking platform perfect for basic fleet tracking, as well as gps tracking for personal use.



# FLASH TRAC OBD

#### Flash Trac OBD Hardware:

The Flash Trac OBD hardware component is small sized, easy to install, tracking device with superior GPS performance. This gps tracker includes a back-up battery, 3-axis accelerometer for motion sense, ultra low power consuming sleep modes, and is compatible to work with both 2G and 3G networks. The Flash Trac OBD installs in seconds in most all passenger vehicles and light duty trucks manufactured after 1996.

### Flash Trac Web Based Tracking Portal:

The Flash Trac portal is an intuitive and a very easy to use interface, that can be accessed from any computer or mobile device with Internet access. As a registered user on the system, you are assigned a unique username/password, which allows you to access your secure account and view your vehicle's location in real-time, as well as its driving history.

#### **Flash Trac Features:**

| Real-Time GPS Tracking                                 |
|--|
| No Contract Low Pricing                                |
| Real-Time Alerts: Speed, Landmarks, Tampering, Voltage |
| Historical View  |
| 30 Day Money Back Guarantee                            |
| Battery Back-Up  |
| Low Battery Alerts                                     |

#### Flash Trac OBD Device Specifications:

| GPS Technology         | GPS   |
|------------------------|---|
| Receiver               | 50 channels   |
| Tracking Sensitivity   | -162 dBm  |
| Location Accuracy      | 2.0 meters  |
| Input Voltage          | 9-16 VDC (start-up, operating)                                |
| Battery Back-Up        | Lithium-Ion 200 mAh   |
| Dimensions             | 1.7" x 2.5" x 0.98" (LxWxH)                                   |
| Weight                 | 1.8 oz  |
| GPS Antenna            | Internal  |
| Cellular Antenna       | Internal  |
| Voltage                | Monitored and Low Battery Notification                        |
| Store & Forward        | Up to 2,000 buffered messages (when out of cellular coverage) |
| Accelerometer          | 3-axis accelerometer for motion sense and tilt                |
| <b>Connection Type</b> | OBD Plug & Play   |
| <b>Operating Temp</b>  | -22 to 167 F  |
| Shock & Vibration      | SAEJ1455  |
| Certifications         | FCC, CE, IC and PTCRB   |
|                        |   |

Direct: 1.661.294.6805 Toll Free: 1.888.544.0494 info@liveviewgps.com